

NB camera lens

Administrator

03 2012 10:31 - 03 2012 17:26



NB camera lens								
Pixel	Size	Sensor	TTL	Image Circle	Structure	Fno	FOV	BFL
VGA	1/4"	OV7725	4.85	5.07	2P	2.8	59	-
		OV7725	4.35	5.1	3P	2.4	65	-
		OV7725	4.22	5.1	3P	2	65	1.09
		OV7725	4.2	5.1	3P	2	65	1.09
		M1360	4.73	5.07	2P	2.8	55.5	1.047
		M1360	4.069	5.1	3P	2	62.27	0.925
	1/6"	M1360	4.95	4.88	3P	2	60	1.46
		OV7670	3.14	3.18	3P	2	63.9	1.12
		OV7670	3.45	3.18	2P	2.8	56	1.288
		M1380	2	2	2P	2	57.8	0.785
1.3M	1/4"	M11320	4.86	4.8	3P	2	60	-
		M11360	4.07	5.1	3P	2	62.27	0.925
		M11320	4.95	5.51	3P	2	61.4	1.46
		OV9655	5.05	5.51	3P	2	66	1.73
	1/5.5"	OV9660	3.25	3.58	3P	2	66	1.15
	1/6"	M11330	3	3.18	3P	2	65.4	0.9
2M	1/4"	M12020	4.86	4.8	3P	2	57.8	1.41
	1/5"	OV2650	3.66	3.8	3P	2	60.9	1.26
New development - Reflowable lens								
The reflowable lens unit would be able to use reflow soldering process with the durability to withstand temperature of 270°C for installing the lenses in mobile camera phones.								